



RO-FLEX 2464-1007T

RO-FLEX 2464-1007TS

Table with columns: 商品 (Part Number), 公称 (Nominal Cross Sectional Area), 導體素線 (Conductor Composition), 絶縁 (Insulation Diameter), 芯数 (No. of Cores), 仕上 (Approx. Outside Diameter), 概算 (Approx. Weight), 電氣特性 (Electrical Properties) including 許容電流 (Current Carrying Capacities), 導体抵抗 (Conductor Resistance), and 絶縁抵抗 (Insulation Resistance).

Table with columns: 商品 (Part Number), 公称 (Nominal Cross Sectional Area), 導體素線 (Conductor Composition), 絶縁 (Insulation Diameter), 芯数 (No. of Cores), シールド (Screen), 仕上 (Approx. Outside Diameter), 概算 (Approx. Weight), 電氣特性 (Electrical Properties) including 許容電流 (Current Carrying Capacities), 導体抵抗 (Conductor Resistance), and 絶縁抵抗 (Insulation Resistance).

●注釈: 1.UL/c-ULの為、153m(500ft)、305m(1000ft)、610m(2000ft)で販売されます。
他の長さについてはお尋ねください。
●Caution: 1.Due to UL/c-UL approval, these cables only deliver in 153m(500ft), 305m(1000ft), 610m(2000ft).
if you would like to get the other length of cables, please ask the sales dept.
★本カタログの製品の仕様は、規格、品質、性能向上の為予告なく変更することがございます。
Specifications of cables in this catalogue will be changed without any notice, because of standard, quality and characteristics improvement.

お問い合わせ先

販売元
中央電材株式会社
〒196-0015 東京都昭島市昭和町4-1-27
Tel 042-543-1141 Fax 042-544-0272
URL: www.chuo-dz.co.jp
製造元
日合通信電線株式会社